余姚市宝利净水设备有限公司

YUYAO POLY WATER PURIFYING SYSTEMS CO.,LTD.

地址: 浙江省余姚市经济开发区(B)区横一路68号
Add:No.68,hengyi road,Yuyao Economic Developing Zone (B),Zhejiang,China
电话(Tel):0086-574-62816125 / 62839197 / 62839196
传真(Fax):0086-574-62813208 / 62839197
E-mail:Lmwater@cnool.net
Chinese language:bf-huang@126.com
Http://www.poly-water.com

POLY 宝利净水
WATER PURIFYING

余姚市宝利净水设备有限公司

YUYAO POLY WATER PURIFYING SYSTEMS CO.,LTD.

POLY 宝利净水
WATER PURIFYING

Company Profile

Yuyao Poly water purifying systems Co.,Ltd.which located in yuyao city,the hometown of mould and plastic in china,only 50KM away from Ningbo airport,cost two hours from Shanghai to our factory,It's specializes in manufacturing water purifying equipments:RO water system,counter top water purifier,tap water filter,filter housing,filter cartrdge,pitcher, quick fitting and other water filter parts.

"support good quality and good price to our custom"is our principle,we keeping it from we established our factory.It made us enjoy good evaluation from our custom,now we start to do business with foreign country not only with the Chinese trade company,so welcome to visit our factory.

RO-01

Description: 5 stage RO system with Auto-Flush
Capacity: 50 GPD(75G/100G)
Flush type: Manual-Flush
Power supply: 220/110V 50/60Hz
Ro membrane: VONTRON or CSM or FCS or FILMTEC
Housing: 10" single "O" ring housing(can be chosen)
Pump: Diaphragm booster pump with adapter
Fitting type: JACO
Faucet: Can be chosen in faucet page
Pressure tank: 3.2G steel tank or 4.0G plastic tank
Unit packing: 41x35x58cm

RO-02

Description: 5 stage RO system with Quick fitting
Capacity: 50 GPD
Flush type: Manual-Flush
Power supply: 220/110V 50/60Hz
Ro membrane: VONTRON or CSM or FCS or FILMTEC
Housing: 10" double "O" ring housing(can be chosen)
Pump: Diaphragm booster pump with adapter
Fitting type: Quick fitting
Faucet: Can be chosen in faucet page
Pressure tank: 3.2G steel tank or 4.0G plastic tank
Unit packing: 41x35x58cm

RO-03

Description: 5 stage RO system with digital display
Capacity: 50 GPD(75G/100G)
Flush type: Auto-Flush controlled by microcomputer
Power supply: 220/110V 50/60Hz
Ro membrane: VONTRON or CSM or FCS or FILMTEC
Housing: 10" single "O" ring housing(can be chosen)
Pump: Diaphragm booster pump with adapter
Fitting type: JACO
Faucet: Can be chosen in faucet page
Pressure tank: 3.2G steel tank or 4.0G plastic tank
Unit packing: 41x35x58cm

RO-04

Description: 5 stage RO system with UV
Capacity: 50 GPD
Flush type: Manual-Flush
Power supply: 220/110V 50/60Hz
Ro membrane: VONTRON or CSM or FCS or FILMTEC
Housing: 10" single "O" ring housing(can be chosen)
Pump: Diaphragm booster pump with adapter
Fitting type: JACO
Faucet: Can be chosen in faucet page
Pressure tank: 3.2G steel tank or 4.0G plastic tank
Unit packing: 41x35x58cm

RO WATER SYSTEM

RO-05

Description: 5 stage RO system with Auto-Flush
Capacity: 50 GPD(75G/100G)
Flush type: Manual-Flush
Power supply: 220/110V 50/60Hz
Ro membrane: VONTRON or CSM or FCS or FILMTEC
Housing: 10" single "O" ring housing(can be chosen)
Pump: Diaphragm booster pump with adapter
Fitting type: JACO
Faucet: Can be chosen in faucet page
Pressure tank: 3.2G steel tank or 4.0G plastic tank
Unit packing: 41x35x58cm

RO-06

Description: 5 stage RO system with Auto-Flush
Capacity: 50 GPD(75G/100G)
Flush type: Manual-Flush
Power supply: 220/110V 50/60Hz
Ro membrane: VONTRON or CSM or FCS or FILMTEC
Housing: 10" single "O" ring housing(can be chosen)
Pump: Diaphragm booster pump with adapter
Fitting type: JACO
Faucet: Can be chosen in faucet page
Pressure tank: 3.2G steel tank or 4.0G plastic tank
Unit packing: 41x35x58cm

RO-07

No need booster pump and storage tank,use low pressure RO membrane

Packing:40x20x47CM/PC

UF-01

The UF-plus water purifier is combined with PP sedment, granular carbon,block carbon,Ultra filter and inline post carbon.the ultra filter can remove the dissolved solids, organics,bacteria etc.it is easy to install and operate

Packing:40x20x47CM/PC

DOUBLE &TRIPLE BB HOUSING FILTER
可做前置过滤器

Choose to buy accessories:

10BBD-2H
Packing:40x23.5x39cm/1PC

10BBD-3H
Packing:58x23.5x39cm/1PC

20BBD-2H
Packing:40x23.5x65cm/1PC

20BBD-3H
Packing:58x23.5x65cm/1PC

Choose to buy accessories:

10BBR-2H
Packing:40.5x23.5x48cm/1PC

10BBR-3H
Packing:58.5x23.5x48cm/1PC

20BBR-2H
Packing:40.5x23.5x72.5cm/1PC

10BBR-3H
Packing:58.5x23.5x72.5cm/1PC

SINGLE O-RING BIG BLUE HOUSING
单O大胖滤瓶

Choose to buy accessories:

For single For double For triple Wrench Screw

HS-10BB01
Jumbo blue housing
Material: Polypropylene
In&outlet: 3/4''or1''NPT plastic
Max working pressure: 125 PSI
Length:10"
Packing:39x39x37cm/4PCS

HS-10BB02
Jumbo blue housing
Material: Polypropylene
In&outlet: 3/4''or1''NPT brass
Max working pressure: 125 PSI
Length:10"
Packing:39x39x37cm/4PCS

HS-20BB01
Jumbo blue housing
Material: Polypropylene
In&outlet: 3/4''or1''NPT plastic
Max working pressure:125 PSI
Length:20"
Packing:39x39x64cm/4PCS

HS-20BB02
Jumbo blue housing
Material: Polypropylene
In&outlet: 3/4''or1''NPT brass
Max working pressure:125 PSI
Length:20"
Packing:39x39x64cm/4PCS

HS-10BB01W
Jumbo blue housing
Material: Polypropylene
In&outlet: 3/4''or1''NPT plastic
Max working pressure: 125 PSI
Length:10"
Packing:39x39x37cm/4PCS

HS-20BB01W
Jumbo blue housing
Material: Polypropylene
In&outlet: 3/4''or1''NPT plastic
Max working pressure:125 PSI
Length:20"
Packing:39x39x64cm/4PCS

HS-10BB01S
Jumbo blue housing
Material: Polypropylene
In&outlet:1.5" NPT plastic
Max working pressure: 125 PSI
Length:10"
Packing:39x39x39cm/4PCS

HS-20BB01S
Jumbo blue housing
Material: Polypropylene
In&outlet:1.5" NPT plastic
Max working pressure: 125 PSI
Length:10"
Packing:39x39x66cm/4PCS

DOUQFE O-RING BIG BLUE HOUSING
双O大胖滤瓶

Choose to buy accessories:

For single For double For triple Wrench Screw

HS-10BB01D
Jumbo blue housing
Material: Polypropylene
In&outlet: 3/4",1" or 1.5"NPT plastic
Max working pressure: 125 PSI
Length:10"
Packing:39x39x37cm/4PCS

HS-10BB02D
Jumbo blue housing
Material: Polypropylene
In&outlet: 3/4''or1''NPT brass
Max working pressure: 125 PSI
Length:10"
Packing:39x39x37cm/4PCS

HS-20BB01D
Jumbo blue housing
Material: Polypropylene
In&outlet: 3/4",1" or 1.5"NPT plastic
Max working pressure:125 PSI
Length:20"
Packing:39x39x64cm/4PCS

HS-20BB02D
Jumbo blue housing
Material: Polypropylene
In&outlet: 3/4''or1''NPT brass
Max working pressure:125 PSI
Length:20"
Packing:39x39x64cm/4PCS

HS-10BB01T
Jumbo transprete housing
Cover material: Polypropylene
Body material: Styrene-acrylonitrile
In&outlet: 3/4",1" or 1.5"NPT plastic
Max working pressure:125 PSI
Length: 10''
Packing:39x39x37cm/4PCS

HS-10BB02T
Jumbo transprete housing
Cover material: Polypropylene
Body material: Styrene-acrylonitrile
In&outlet: 3/4''or1''NPT plastic
Max working pressure:125 PSI
Length: 10''
Packing:39x39x37cm/4PCS

HS-20BB01T
Jumbo transprete housing
Cover material: Polypropylene
Body material: Styrene-acrylonitrile
In&outlet: 3/4",1" or 1.5"NPT plastic
Max working pressure:125 PSI
Length: 20''
Packing:39x39x64cm/4PCS

HS-20BB02T
Jumbo transprete housing
Cover material: Polypropylene
Body material: Styrene-acrylonitrile
In&outlet: 3/4''or1''NPT plastic
Max working pressure:125 PSI
Length:20''
Packing:39x39x64cm/4PCS

COUNTER TOP WATER FILTER/WALL MOUNTED

CWF-07
Cartridge:PP or carbon block
Packing:50x30x36cm/8PCS

CWF-08
Cartridge:PP+carbon block
Packing:50x30x36cm/4PCS

CWF-09
Cartridge:PP+carbon block+UDF
Packing:58x43x36cm/4PCS

CWF-12
Cartridge:PP or carbon block
Packing:50x30x36cm/8PCS

CWF-03
Cartridge:PP+carbon block
Packing:50x30x36cm/4PCS

CWF-13
Cartridge:PP+carbon block+UDF
Packing:58x43x36cm/4PCS

WM-01
Cartridge:PP+carbon block
Packing:59.5x36x38cm/4PCS

WM-02
Cartridge:PP+carbon block+UDF
Packing:59.5x46.5x38.5cm/4PCS

SHOWER FILTER 沐浴器

FSH-03
Packing:39x39x29cm/50PCS
In&outlet:1/2 inch

FSH-02
Packing:39x39x29cm/50PCS
In&outlet:1/2 inch

FSH-04
Packing:50x50x15.5cm/25PCS
In&outlet:1/2 inch

FSH-01
Packing:50x50x15.5cm/25PCS
In&outlet:1/2 inch

FSH-05
Packing:39x39x29cm/50PCS
In&outlet:1/2 inch

FSH-06
Packing:39x39x29cm/50PCS
In&outlet:1/2 inch

FSH-07
Packing:50x50x15.5cm/25PCS
In&outlet:1/2 inch

FSH-08
Packing:50x50x15.5cm/25PCS
In&outlet:1/2 inch

KDF FUNCTION:
1. Strain away 95% residual chlorine of water.
2. Strain away heavy metal ions such as Zn2+,Hg2+,Cu2+,Cd2+...of 90% or more.
3. Strain away hazardous substance in the water, such as Cr6+,As...and so on.
4. Restrain the reproduction of bacterium and virus.
5. Scale inhibition Effection

GRANULAR ACTIVE CARBON FUNCTION:
Remove chlorine,bad odor,improve the taste

Use shower filter avoid the skin itch infect skin sickness

Kinds of shower filter cartridge:
1.coconut active carbon
2.coconut active carbon&KDF(10%)
3.coconut active carbon&KDF(10%)&Bio-ceramic(50%)

FSH-01/04/07/08 Cartridge
Packing:38x38x46.5cm/100PCS

FSH-02/03/05/06 Cartridge
Packing:35x35x39cm/100PCS

Plastic connect fitting
Connect size:1/2 inch

Copper connect fitting
Connect size:1/2 inch

TWF-01
Packing:37.5x27x59cm/50PCS

TWF-04
Packing:37.5x27x59cm/50PCS

TWF-02
Packing:37.5x27x59cm/50PCS

TWF-05

TWF-06
Packing:33x26.5x42cm/20PCS

TWF-07
Packing:33x26.5x42cm/20PCS

connect for TWF-05

connect for TWF-06/07

connect for TWF-06/07

connect for TWF-06/07

cartridge for TWF-06/07

Filter cartridge for TWF-01/02/04
Packing:29X23.5X37cm/100PCS

The product adopts the most advanced ion-exchange and activated carbon adsorption technology to perfor water purification fuction . activated carbon which can efficiently remove the small molecular organic substance,residual chlorine, and other can improve water taste

Kinds of the filter cartridge:
1.coconut active carbon
2.coconut active carbon&resin(10%).

DSV-01

Round solenoid valve(Thread)
Packing:100pcs/45*18.5*17.3CM
Input power 4.8W
Voltage:DC12V,DC24V,DC36V
Frequency:50-60HZ
Working water pressure:0-0 8Mpa

DSV-02

Round solenoid valve(Quick fitting)
Packing:100pcs/45*18.5*17.3CM
Input power 4.8W
Voltage:DC12V,DC24V,DC36V
Frequency:50-60HZ
Working water pressure:0-0 8Mpa

DSV-03

18 seconds Auto flush valve(Quick fitting)
Packing:100pcs/28*22.5*38.5CM
Input power 4.8W
Voltage:DC12V,DC24V,DC36V
Frequency:50-60HZ
Working water pressure:0-0 8Mpa
Connection type:1/4QC

DSV-04

Water inlet valve(Thread)
Packing:100pcs/32*32*18.5CM
Input power 4.8W
Voltage:DC12V,DC24V,DC36V
Frequency:50-60HZ
Working water pressure:0-0 8Mpa
Port:NPT 1/4"

WSF-02
Packing:40x40x30cm/50PCS
In&outlet:3/4 inch

Material inside:phosphate
Phosphate function:
Remove Calcium&Magnesium,avoide equipment rusting and forming limescle

DSV-05

Water inlet valve(Quick fitting)
Packing:100pcs/32*32*18.5CM
Input power 4.8W
Voltage:DC12V,DC24V,DC36V
Frequency:50-60HZ
Working water pressure:0-0 8Mpa
Port:QC 1/4"

DSV-06

Water inlet valve(Quick fitting)
Packing:100pcs/32*32*18.5CM
Input power 4.8W
Voltage:DC12V,DC24V,DC36V
Frequency:50-60HZ
Working water pressure:0-0 8Mpa
Port:QC 3/8"

FILTER HOUSING

HS-03
White colour
Material:
Polypropylene
In&outlet:
1/4" NPT plastic port
Double "O" ring
Packing:
47x36x33cm/12PCS

HS-26
Transparent colour
Cover material:
Polypropylene
Body material:
Styrene-acrylonitrile
In&outlet:
1/4" NPT plastic port
Double "O" ring
Packing:
47x36x33cm/12PCS

HS-07
White colour
Material:
Polypropylene
In&outlet:
1/4"or 1/2" NPT plastic port
Packing:
47x36x33cm/12PCS

HS-27
Transparent colour
Cover material:
Polypropylene
Body material:
Styrene-acrylonitrile
In&outlet:
1/4"or 1/2" NPT plastic port
Packing:
47x36x33cm/12PCS

HS-08
Blue colour
Material: Polypropylene
In&outlet:
1/2"or 3/4"or 1" NPT Plastic port or brass port
Packing:
57x43x35.5cm/12PCS

HS-23
Length:5 inch
Packing:
30x43.5x57cm/12PCS

HS-31
In&outlet:
1/2"NPT brass port

HS-32
In&outlet:
1/2"NPT brass port

HS-11
Material:nylon(for hot water)
In&outlet:
1/2"or 3/4" or 1" brass port
Max working pressure:290 PSI
Max working temperature:
216°F/90°C
Length:10"
Packing:57x43x34cm/12PCS

HS-11B
Material:nylon(for hot water)
In&outlet:
1/2"or 3/4" or 1" brass port
Max working pressure:290 PSI
Max working temperature:
216°F/90°C
Length:10"
Packing:57x43x34cm/12PCS

HS-17
Black cover&
Transprate body
Material:
Polypropylene
In&outlet:
1/2"or 3/4" or 1" NPT Plastic port or brass port
Packing:
57x43x35.5cm/12PCS

HS-14
Blue cover&
Transparent body
Cover material:
Polypropylene
Body material:
Styrene-acrylonitrile
In&outlet:
1/2"or 3/4"or 1" NPT Plastic port or brass port
Packing:
57x43x35.5cm/12PCS

HS-24
Blue cover &
Transparent body
Cover material:
Polypropylene
Body material:
Styrene-acrylonitrile
In&outlet:
1/2" or 3/4" or 1" NPT brass port
Packing:
58.5x44x34cm/12PCS

HS-24B
Blue cover &
Blue body
Cover material:
Polypropylene
Body material:
Polypropylene
In&outlet:
1/2" or 3/4" or 1" NPT brass port
Packing:
58.5x44x34cm/12PCS

HS-24R
Red cover &
Red body
Cover material:
Polypropylene
Body material:
Polypropylene
In&outlet:
1/2" or 3/4" or 1" NPT brass port
Packing:
58.5x44x34cm/12PCS

ST-10A
Cover material:copper
Body Material:
304 stanless steel
In&outlet:1/2",3/4"
Length:10" or 20"
Packing:23x57x37cm/10PCS

ST-10B
Cover material:plastic
Body material:
304 stanless steel
In&outlet:1/2",3/4"
Length:10" or 20"
Packing:23x57x37cm/10PCS

ST-10BB
Jumbo housing
Cover material: Copper
Body material:
304 stanless steel
In&outlet: 1"
Length:10"
Packing:36x36x38cm/4PCS

ST-20BB
Jumbo housing
Cover material: Copper
Body material:
304 stanless steel
In&outlet: 1"
Length: 20"
Packing:36x36x65cm/4PCS

FILTER HOUSING

The HS-19/20 series filter housing can not be installed with general cartridges of 5 inch; they can be only installed with the following cartridge:
Inner diameter:20mm;
Out diameter:48mm,
Length:5 inch,housing size:5 inch,
Connector size:1/2 inch

HS-24T
PET材质滤瓶
包装尺寸：58.5x44x34厘米/箱
12只/箱

HS-28B
Blue cover &
Blue body
Cover material:
Polypropylene
Body material:
Polypropylene
In&outlet:
1/2"or 3/4"or 1"NPT brass port
Packing:
72x30x35cm/5PCS

HS-28
Blue cover &
Transparent body
Cover material:
Polypropylene
Body material:
Styrene-acrylonitrile
In&outlet:
1/2"or 3/4"or 1"NPT brass port
Packing:
72x30x35cm/5PCS

HS-25
Black cover&blue body
Material: Polypropylene
In&outlet:3/8",1/2", 3/4", 1"
NPT brass port
Length:20"
Packing:41x27x59cm/6PCS

HS-25T
Black cover&Transprate body
Cover material: Polypropylene
Body material: Styrene-acrylonitrile
In&outlet:3/8",1/2", 3/4", 1"
NPT brass port or plastic port
Length:20"
Packing:41x27x59cm/6PCS

HS-25B
Triple 20" Slim Housing
Packing:
42x31x62cm/2PCS

HS-25R
Triple 20" Slim Housing
Packing:
42x31x62cm/2PCS

CARBON BLOCK

The carbon block cartridge is sintered or extruded by high quality activated carbon.it can be made of the various carbon media,such as:coal carbon ,fruit shell carbon and coconut carbon.the CTO cartridge is suitable for the water treatment for removeing the chlorine,taste,and odor.

CTO-5
Media:coal carbon,fruit shell carbon or coconut carbon
Length:5 inch
Packing:37x37x28cm/50PCS
In diameter:28mm
Out diameter:70mm

CTO-10
Media:coal carbon,fruit shell carbon or coconut carbon
Length:10 inch
Packing:37x37x26.5cm/25PCS
Out diameter:70mm

CTO-20
Media:coal carbon,fruit shell carbon or coconut carbon
Length:20 inch
Packing:37x37x53cm/25PCS
In diameter:28mm
Out diameter:70mm

CTO-10BB
Media:coal carbon,fruit shell carbon or coconut carbon
Length:10 inch
Packing:61x25x27cm/10PCS
In diameter:28mm
Out diameter:4.5 inch/114mm

CTO-20BB
Media:coal carbon,fruit shell carbon or coconut carbon
Length:20 inch
Packing:36x24.5x53cm/6PCS
In diameter:28mm
Out diameter:4.5 inch/114mm

CTO-10M
Media:coal carbon,fruit shell carbon or coconut carbon
Packing:50x25x26.5cm/50PCS

The granular carbon filter cartridge is made up of the granular carbon media and the food grade housing.it can remove the chlorine,taste,and odor from the water. According to the requirements,various types and sizes are available for option.
Length:5,10,20 inch'
Out diamenter:2.5,4.5 inch

GAC-10M
Packing:
50x25x26.5cm/50PCS

GAC-10F
Packing:
33x28x53cm/40PCS

GAC-20F
Packing:
33x28x53cm/20PCS

UDF-5
Length:5 inch
Packing:
37x37x53cm/100PCS

UDF-10
Length:10 inch
Packing:
37x37x28cm/25PCS

UDF-20
Length:20 inch
Packing:
33x28x53cm/20PCS

GAC-10Y
Length:10 inch
Packing:
37x37x26.5cm/25PCS

GAC-10C
Length:10 inch
Packing:
37x37x26.5cm/25PCS

GAC-20C
Length:20 inch
Packing:37x37x53cm/25PCS

GAC-10CBB
Length:10 inch
Packing:49x37x27cm/12PCS

GAC-20CBB
Length:20 inch
Packing:36x24x53cm/6PCS

GAC-10BBY
Length:10 inch
Packing:
49x37x27cm/12PCS

GAC-20BBY
Length:20 inch
Packing:
36x24x53cm/6PCS

UDF-10BB01
Length:10 inch
Packing:
49x37x27cm/12PCS

UDF-20BB01
Length:20 inch
Packing:
36x24x53cm/6PCS

UDF-10BB02
Length:10 inch
Packing:
49x37x27cm/12PCS

UDF-20BB02
Length:20 inch
Packing:
36x24x53cm/6PCS

ROH membrane housing is designed for RO membrane,which is made of FDA inspection stand PP material.Its steady and simple structure makes it hold the RO membrane perfectly.
The standard port:1/4 inch

GAC-10A
Length:10 inch
Packing:
38x38x28cm/25PCS

GAC-10E
Length:10 inch
Packing:
39x39x28cm/25PCS

UDF-10R
Length:10 inch
Packing:
38x38x28cm/25PCS

RSN-10
Length:10 inch
Packing:
38x38x28cm/25PCS

UDF-10BBR
Length:10 inch
Packing:
49x37x27cm/12PCS

UDF-20BBR
Length:20 inch
Packing:
36x24x53cm/6PCS

Phosphate filter cartridge is made up of phosphate and SAN material housing.it can hinder the dirt,antisepticise and improve water quality.
The resin filter cartridge is made up of ion exchange resin and SAN material housing.it removes calcium and magnesium ions from waterby exchangeing them with harmless sodium ion.

NS-10C
Length:10 inch
Packing:
38x38x28cm/25PCS

NS-10D
Length:10 inch
Packing:
38x38x28cm/25PCS

T33-10-4
Length:10 inch
Packing:
28.5x26.5x25cm/25PCS

T33-10GS
Length:10 inch
Packing:
28.5x26.5x25cm/25PCS

T33-10G
Length:10 inch
Packing:
28.5x26.5x25cm/25PCS

T33-10P
Length:10 inch
Packing:
28.5x26.5x25cm/25PCS

The post inline filter cartridge and inline filter cartridge are usually used as for the last stage of the RO system.It is filled in with different media such as carbon block,active carbon,PP sedment, which have fine effect of filtration for removing the chlorine,taste,and odor.

T33-5A
Length:5 inch
Packing:
45x28x17.5cm/40PCS

T33-7S
Packing:
30x26.5x25cm/25PCS

T33-10F
Packing:
28.5x26.5x25cm/25PCS

T33-10B
Packing:
28.5x26.5x25cm/25PCS

T33-10BS
Packing:
28.5x26.5x25cm/25PCS

T33-10C
Packing:
54x29.5x30cm/40PCS

T33-10D
Packing:
54x29.5x30cm/40PCS

T33-10EQ
Packing:
55x27.5x25cm/50PCS

T33-10E
Packing:
55x26.5x25cm/50PCS

QTC-01
快插式PP滤芯

QTC-02
快插式碳棒滤芯

QTC-03
快插式活性炭滤芯

SQT-01
快插式碳棒滤芯

SQT-02
快插式活性炭滤芯

SQT-03
快插式PP滤芯

ROH-01
Packing:
56.5x42x33cm/40PCS

ROH-02
Packing:
56.5x42x33cm/40PCS

TT-5
Length:5 inch
Packing:
33x33x53cm/100PCS

TT-10
Length:10 inch
Packing:
33x33x53cm/50PCS

TT-20
Length:20 inch
Packing:
33x33x53cm/25PCS

FILTER CARTRIDGE

PP filter cartridge ,which is made of plypropylene,can remove the particles,impurities and dust in the water.
Filtration precision:1,5,10.20 50 micron
Length:10,20,30,40inch

PP-10M
Packing:
50x25x26.5cm/
50PCS

PP-10
(ϕ 55)
Length:10 inch
Packing:
28x28x52cm
/50PCS

PP-10
(ϕ 58)
Length:10 inch
Packing:
29x29x52cm
/50PCS

PP-10
(ϕ 60)
Length:10 inch
Packing:
31x31x52cm
/50PCS

PP-10
(ϕ 63)
Length:10 inch
Packing:
33x33x52cm
/50PCS

PP-10G
Length:10 inch
Packing:
34x34x54cm/50PCS

PP-20
Length:20 inch
Packing:
34x34x54cm/25PCS

PP-10BB
Length:10 inch
Packing:
59x24x53cm/20PCS

PP-20BB
Length:20 inch
Packing:
59x24x53cm/10PCS

PPC filter cartridge is stringed by the polypropylene thread symmetrically.can remove the particles,impurities and dust in the water.
Filtration precision:1,5,10.20 50 micron
Length:10,20,30,40inch

PPW-10
(ϕ 55)
Length:10 inch
Packing:
28x28x52cm/50PCS

PPW-10
(ϕ 58)
Length:10 inch
Packing:
29x29x52cm/50PCS

PPW-10
(ϕ 60)
Length:10 inch
Packing:
31x31x52cm/50PCS

PPW-10
(ϕ 63)
Length:10 inch
Packing:
33x33x52cm/50PCS

PPW-20
Length:20 inch
Packing:
33x33x53cm/25PCS

PPW-10BB
Length:10 inch
Packing:
59x24x53cm/20PCS

PPW-20BB
Length:20 inch
Packing:
59x24x53cm/10PCS

PPC pleated cartridge is made various materials like as:PP,PES,NILON,and PVDF.this filter cartridge have high efficiency precision is suitable for industrial,medicine and potable water treatment.
Filtration precision:1,5,10,50micron
Length:10,20inch
Max working temperature:120F
Max working pressure:125psi

PPC-10
Length:10 inch
Packing:
33x33x53cm/50PCS

PPC-10P
Length:10 inch
Packing:
39x39x28cm/25PCS

PPC-10BB
Length:10 inch
Packing:
39x39x53cm/18PCS

PPC-20
Length:20 inch
Packing:
33x33x53cm/25PCS

PPC-20P
Length:20 inch
Packing:
38x38x53cm/25PCS

PPC-20BB
Length:20 inch
Packing:
39x39x53cm/9PCS

CARBON BLOCK + SEDMENT
复合滤芯

材质：外层烧结碳，内层PP滤芯
功能：采用真正的烧结碳棒，去除余氯能力超强，在通过8吨水后，求出余氯依然大于50%，内层防止pp滤芯，真正实现一根滤芯双重过滤效果。

CTO-10D

STEEL BRACKET

BRK-01
For single BB Housing

BRK-02
For single 10",20" slim Housing

BRK-03
For double BB Housing

BRK-04
For RO water system

BRK-05
For double wall mounted filter

BRK-06
For double counter top filter

BRK-07
For triple BB Housing

BRK-08
For triple wall mounted filter

BRK-09
For triple counter top filter

BRK-10
For double 10" BB Housing

BRK-11
For triple 10" BB Housing

BRK-12
For double 20" BB Housing

BRK-13
For triple 20" BB Housing

"L" 型外螺纹接头 MALE ELBOW ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Outside Thread 外螺纹 (B)
QF002-A	1/4	1/4
QF002-B	1/4	1/2
QF002-C	3/8	1/4
QF002-D	3/8	3/8
QF002-E	3/8	1/2
QF002-F	5/16	3/8
QF002-G	5/16	1/4

"L" 型插栓 PLUG ELBOW ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	StemO.D 插栓 (B)
QF003-A	1/4	1/4
QF003-B	1/4	3/8
QF003-C	3/8	1/4
QF003-D	3/8	3/8

"L" 型双通弯头 ELBOW ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Tube O.D 管子 (B)
QF004-A	1/4	1/4
QF004-B	1/4	3/8
QF004-C	3/8	3/8
QF004-D	5/16	5/16
QF004-E	5/16	1/4
QF004-F	5/16	3/8

"L" 型外螺纹接头 MAIE EIBOW ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Outside Thread 外螺纹 (B)
QF005-A	1/4	3/8
短 QF005-B	1/4	3/8

"一" 型双通接头 STRAIGHT ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Tube O.D 管子 (B)
QF006-A	1/4	1/4
QF006-B	1/4	3/8
QF006-C	3/8	3/8
QF006-D	5/16	5/16
QF006-E	5/16	1/4
QF006-F	5/16	3/8

正 "T" 型三通接头 MALE TEE ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Outside Thread 外螺纹(B)	Tube O.D 管子 (C)
QF007-A	1/4	1/4	1/4
QF007-B	1/4	3/8	1/4
QF007-C	1/4	1/4	3/8
QF007-D	1/4	3/8	3/8
QF007-E	3/8	3/8	3/8
QF007-F	3/8	1/4	3/8

正 "T" 型三通接头 MALE TEE ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Tube O.D 管子 (B)	Outside Thread 外螺纹 (C)
QF008-A	1/4	1/4	1/4
QF008-B	1/4	1/4	3/8
QF008-C	1/4	3/8	3/8
QF008-D	3/8	1/4	1/4
QF008-E	3/8	3/8	3/8
QF008-F	3/8	1/4	3/8
QF008-G	1/4	3/8	1/4
QF008-H	3/8	3/8	1/4

"T" 型管三通接头 TEE ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Tube O.D 管子(B)	Tube O.D 管子(C)
QF008-A	1/4	1/4	1/4
QF008-B	1/4	1/4	3/8
QF008-C	1/4	3/8	1/4
QF008-D	1/4	3/8	3/8
QF008-E	3/8	3/8	3/8
QF008-F	3/8	1/4	3/8
QF008-G	5/16	5/16	5/16
QF008-H	5/16	1/4	1/4
QF008-I	5/16	1/4	5/16
QF008-J	5/16	5/16	1/4
QF008-L	1/4	5/16	1/4

"T" 型插栓 PLUGIN TEE ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Stem O.D 插栓 (B)	Tube O.D 管子 (C)
QF010-A	1/4	1/4	1/4
QF010-B	1/4	1/4	3/8
QF010-C	3/8	1/4	3/8
QF010-D	3/8	3/8	3/8
QF010-E	1/4	3/8	3/8
QF010-F	1/4	3/8	1/4

"一" 字型外螺纹接头 MALE STRAIGHT ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Outside Thread 外螺纹 (B)
QF011-A	1/4	1/8

"一" 字型外螺纹接头 MALE STRAIGHT ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Outside Thread 外螺纹 (B)
QF012-A	1/4	1/4
QF012-B	1/4	3/8
QF012-C	3/8	3/8
QF012-D	3/8	1/4
QF012-E	5/16	1/4

"L" 型外螺纹接头 MALE ELBOW ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Outside Thread 外螺纹 (B)
QF013-A	1/4	1/8
QF013-B	3/8	1/8

隔板接头 BUIK HEAD ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Tube O.D 管子 (B)	Thread 螺纹 (C)
QF014-A	1/4	1/4	Φ16.5mm
QF014-B	1/4	3/8	Φ20mm
QF014-C	3/8	3/8	Φ20mm
QF014-D	5/16	5/16	Φ20mm
QF014-E	5/16	1/4	Φ20mm

加长外螺纹接头 MALE ELBOW ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Outside Thread 外螺纹 (B)
QF015-BB	1/4	1/4

球阀 BALL VALVE

PART-NO. 编号	Tube O.D 管子 (A)	Internal thread 内螺纹 (B)
QF015-A	1/4	1/4
QF015-B	3/8	3/8
QF015-C	3/8	1/4

球阀 BALL VALVE

PART-NO. 编号	Tube O.D 管子 (A)	Internal thread 内螺纹 (B)
QF015-D	1/4	1/4
QF015-E	3/8	1/4
QF015-F	3/8	3/8

"T" 型插栓 PLUG TEE ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Tube O.D 管子 (B)	Stem O.D 插栓(C)
QF016-A	1/4	1/4	1/4
QF016-B	1/4	3/8	1/4
QF016-C	3/8	1/4	1/4
QF016-D	3/8	3/8	1/4
QF016-E	3/8	3/8	3/8
QF016-F	1/4	3/8	3/8
QF016-G	3/8	1/4	3/8
QF016-H	1/4	1/4	3/8

"Y" 型管三通接头 TWO WAY DIVIDER

PART-NO. 编号	Tube O.D in 管子 (A)	Tube O.D OUT 管子 (B)	Tube O.D OUT 管子(C)
QF017-A	1/4	1/4	1/4
QF017-B	3/8	3/8	3/8
QF017-C	3/8	1/4	1/4

"L" 型内螺纹接头 FEMALE ELBOW ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Internal thread 内螺纹 (B)
QF018-A	1/4	1/4
QF018-B	1/4	3/8
QF018-C	3/8	1/4
QF018-D	1/4	3/8
QF018-E	1/4	1/2
QF018-F	3/8	3/8

"L" 型内螺纹接头 FEMALE ELBOW ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Internal thread 内螺纹 (B)
QF018-G	3/8	1/2
QF018-H	1/4	7/16-24
QF018-I	3/8	7/16-24
QF018-J	3/8	1/8

直的内螺纹接头 FEMALE STRAIGHT ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Internal thread 内螺纹 (B)
QF019-A	1/4	1/4
QF019-B	3/8	1/4
QF019-C	3/8	3/8
QF019-D	1/4	7/16-24
QF019-E	1/4	1/8
QF019-F	3/8	7/16-24
QF019-G	3/8	1/8
QF019-H	1/4	3/8
QF019-I	5/16	3/8

"L" 型逆止阀接头 CHECK VALVE

PART-NO. 编号	Tube O.D 管子 (A)	Outside Thread 外螺纹 (B)
QF020-A	1/4	1/4
QF020-B	1/4	3/8
QF020-C	3/8	1/4

"一" 字型外螺纹接头 MALE STRAIGHT ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Outside Thread 外螺纹 (B)
QF021-A	1/4	1/2

直的内螺纹接头 FEMALE STRAIGHT ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Internal thread 内螺纹 (B)
QF022-A	1/4	1/2
QF022-B	1/4	M20

"一" 字型外螺纹接头 MALE STRAIGHT ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Outside Thread 外螺纹 (B)
QF023-A	3/8	1/2

直的内螺纹接头 FEMALE STRAIGHT ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Internal thread 内螺纹 (B)
QF024-A	3/8	1/2
QF024-B	3/8	M20

球阀 BALL VALVE

PART-NO. 编号	Tube O.D 管子 (A)	Tube O.D 管子 (B)
QF025-A	1/4	1/4
QF025-B	3/8	3/8
QF025-C	3/8	1/4
QF025-D	5/16	5/16
QF025-E	5/16	3/8
QF025-F	5/16	1/4

直的内螺纹接头 FEMALE STRAIGHT ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Internal thread 内螺纹 (B)
QF026-A	3/8	3/4 英制
QF026-B	1/4	3/4 英制
QF026-C	3/8	3/4 美制
QF026-D	1/4	3/4 美制

"一" 字型插座接头 PLUG ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Plug O.D 插座 (B)
QF028-A	1/4	Φ10mm

双隔板接头 DOUBLE BUIK HEAD ADAPTER

PART-NO. 编号	Tube O.D 管子 (A)	Tube O.D 管子 (B)	Tube O.D 管子 (C)	Tube O.D 管子 (D)
QF029-A	1/4	1/4	1/4	1/4
QF029-B	1/4	1/4	3/8	3/8

快接四面阀 AUTO SHUT-OFF VALVE

PART-NO. 编号	Tube O.D 管子	Pressure difference 压力比
QF030-A	1/4x4	1/2 ± 0.2

快接高压开关 HIGH PRESSURE SWICH

PART-NO. 编号	Tube O.D 管子 (A)	Tube O.D 管子 (B)	Adjustable stamza scope of pressure 压力可调节范围
QF031-A	1/4	1/4	2.0kg~4.5kg

快接低压开关 LOSS PRESSURE SWICH

PART-NO. 编号	Tube O.D 管子 (A)	Start the pressure 启动压力
QF032-A	1/4	≥0.2kg

"一" 字型双通逆止阀接头 CHECK VALVE

PART-NO. 编号	Tube O.D 管子 (A)	Tube O.D 管子 (B)
QF033-A	1/4	1/4
新款QF033-A	1/4	1/4

"一" 字型双通逆止阀接头 CHECK VALVE

PART-NO. 编号	Tube O.D 管子 (A)	Internal thread 内螺纹 (B)
QF033-B	1/4	1/4
QF033-C	3/8	3/8

球阀 BALL VALVE

PART-NO. 编号	Tube O.D 管子 (A)	Outside Thread 外螺纹 (B)
QF034-A	1/4	1/4
QF034-B	3/8	3/8
QF034-C	1/4	3/8
QF034-D	1/4	1/2
QF034-E	3/8	1/2

快接废水夹 WASTE WATER CLAMP

PART-NO. 编号	Tube O.D 管子 (A)	Internal thread 内螺纹 (B)
QF035-A	1/4	Φ40mm
QF035-B	3/8	Φ40mm

快接废水比 WASTE WATER RATIO VALVE

PART-NO. 编号	Tube O.D 管子 (A)	Tube O.D 管子 (B)	Discharge 流量
QF036-A	1/4	1/4	300CC
QF036-B	1/4	1/4	350CC
QF036-C	1/4	1/4	400CC
QF036-D	1/4	1/4	420CC
QF036-E	1/4	1/4	550CC

FCT-04

FCT-03

FCT-01

FCT-05

FCT-02

FCT-06

FCT-07

FCT-08

CN-01

CN-02

CN-03

ADP-01

ADP-02

ADP-05

BV-01
(1/4"X1/4")

BV-02
(1/4"X1/4")

ADP-07

ADP-09

PE TUBE

Ultraviolet Sterilizer

Using ultraviolet equipment is an efficient and rapid method of water disinfection without the use of heat or dangerous chemicals. It utilizes ultraviolet light to disable bacteria quickly and reliably, viruses and other micro-organisms present in water, Its simple operating and maximum efficiency make UV water sterilizer equipment suitable for wide range uses of promoting the quality of the water.

Specification of Ultraviolet Water Sterilizer Assembly							
Tye		UV4W	UV6W	UV11W	UV16W	UV25W	UV30W
Pure water		0.056t/h 0.25GPM	0.11t/h 0.5GPM	0.22t/h 1GPM	0.45t/h 2GPM	1.36t/h 6GPM	1.8t/h 8GPM
Tap water		0.044t/h 0.2GPM	0.08t/h 0.4GPM	0.017t/h 0.8GPM	0.36t/h 1.6GPM	1.0t/h 4.8GPM	1.45t/h 6.4GPM
Lamp rated life(hrs)		8000	8000	8000	8000	8000	8000
UV dosage(uW-sec/cm^2)		>30000	>30000	>30000	>30000	>30000	>30000
Electricity unit	Volts	110-130 200-240	110-130 200-240	110-130 200-240	110-130 200-240	110-130 200-240	110-130 200-240
	Hz	50/60	50/60	50/60	50/60	50/60	50/60
	Watts	4W	6W	11W	16W	25W	30W
Lamp failure Warning system	LED	LED	LED	LED	LED	LED	LED
	Alarm	Alarm	Alarm	Alarm	Alarm	Alarm	Alarm
Timer		NO	NO	NO	NO	NO	NO
No.of UV lamp needed		1	1	1	1	1	1
Overall dimension(mm)		ф51*200	ф51*260	ф51*260	ф64*350	ф64*520	ф64*970
Shell material(stainless)		304#	304#	304#	304#	304#	304#
Inlet/outlet size(inch)		1/4"	1/4"	1/4"	1/4"	1/2"	1/2"
Type of lamp holder		G5	G5	G5	G5	G13	G13
Max operation pressure		6kg	6kg	6kg	6kg	8kg	8kg
UV lamp		PHILIPS HOLLAND	PHILIPS HOLLAND	PHILIPS HOLLAND	PHILIPS HOLLAND	PHILIPS HOLLAND	PHILIPS HOLLAND